

K525i

PROFESSIONAL CHOICE FOR HIGHEST DEMANDS



PRODUCT HIGHLIGHTS

- Maximum optical performance – field of view, high contrast image, high definition
- Absolutely reliable repeat accuracy and precise, clearly defined click mechanism
- Optional left or right side windage
- Parallax wheel integrated into the elevation turret (patented) (20 m to ∞)
- Innovative TWIST GUARD windage (patented)
- Precise illuminated reticle in 1 st focal plane

The K525i combines maximum optical performance and precision with unique handling and ergonomics. A rugged riflescope for professionals, with windage optional left or right, precise illuminated reticles in 1 st focal plane and the unique TWIST GUARD windage.

TECHNICAL DATA

Magnification:	5 - 25
Objective lens diameter:	56 mm
Exit pupil diameter	9.5 - 2.3 mm
Eye relief	95 mm
Field of view:	7.1 - 1.5 m/100 m 21.7 - 4.4 ft/100 yds
Diopter compensation:	+2.0 / -3.5 dpt
Impact correction per click:	0.1 MRAD $\frac{1}{4}$ MOA
Parallax adjustment:	20 m till ∞
Adjustment range (E/W):	104.4/46.8 in/100 yds
Tube diameter:	34 mm
Length:	377 mm 14.8 in
Weight:	970 g 34.2 oz

Illuminated:

yes

Warranty:

10 years

FEATURES



1st focal plane



Main tube 34 mm



Adjustment direction
CW or CCW



MOA or MIL



Windage left or right



Zero Stop




TWIST GUARD
windage


RETICLES




MSR2/Ki



SKMR3



SKMR



MOAK